

Acrysil Barrier

ACRYLIC / SILOXANE HYBRID SEALER

Product Description:

Acrysil Barrier is an advanced hybrid Acrylic + Siloxane sealer offering the perfect blend of surface protection and deep penetration for marble, granite, natural stone and concrete. Its hybrid formula combines the strength of acrylic with the water-repellant properties of siloxane, providing superior durability, stain resistance, and enhancement of natural surfaces.

Recommended Uses:

Marble, granite, slate, travertine, and other natural stones. Concrete surfaces including driveways, walkways and countertops.

Advantages:

- Seals and protects against water and stains.
- UV resistant and prevents yellowing.
- Algae and mold inhibitor.
- Provides a hydrophobic barrier.
- Short-term resistance to oil spill.
- For External and Internal use.

Technical Properties:

Basis	: Siloxane/Acrylic
Colour	: Clear.
Consistency	: Liquid.
pH	: 9.5 ± 0.5
Solid content	: $24 \pm 1.0\%$
Consumption	: 8 to 10 sqm. / ltr. / coat.

Application	: Ready to use (minimum two coats).
Dry to touch	: between 30 mins to 1 hour.
Dry to recoat	: 4 hours.
Open to traffic	: 48 – 72 hours.

Directions for Use:

Clean the surface thoroughly. Remove any dirt, oil or contaminants. Ensure the surface is dry before application.

Application:

Apply an even coat using a sprayer, roller or brush. For porous surfaces, multiple coats are required. Make sure to apply sealer consistently to prevent blotching.

Packaging:

Available in 1 litre bottles, 6 litre cans and 25 litre cans.

Storage & Shelf Life:

Store in a frost-free environment away from direct sunlight and maintain an ambient temperature of 25°C. Given these conditions, it will remain useable for 9 months in the original unopened packaging, use opened packaging promptly.